

QUICKJACK™

Motorcycle Lift

MOTORCYCLE LIFT ADAPTER KIT

The QuickJack Motorcycle Lift Adapter Kit turns your portable car lift into a portable motorcycle service lift. Simply slide the QuickJack frames together, rest the lightweight aluminum platform on top and secure the assembly with a single pass-through locking pin. The stylish cold-formed diamond tread platform is light, easy to transport and made from rugged TIG-welded 6061-T6 aluminum, providing maximum grip and an attractive finish.

Make QuickJack compatible with motorcycles up to 1,000 lbs.

Transform QuickJack into the perfect dual-purpose tool for your bike, and make washing, detailing and servicing chores easier and a lot more enjoyable. The Motorcycle Lift Adapter Kit assembles from storage in just minutes and lifts in seconds flat. The revolutionary QuickJack is the only car lift in the world that you can take anywhere. Add our optional Motorcycle Lift Adapter Kit to your order and double QuickJack's capability. Also great for servicing lawnmowers and other equipment.

These adapter kits feature a front-wheel vise for fast and easy set-up. The rugged wheel vise features a heavy-duty hand crank that adjusts to fit most front wheel sizes while cushioned, treaded rubber pads grip the bike firmly. Dual tie-down rings located right upfront provide the perfect anchor locations for tie-down and ratchet straps.

- Cold-formed and tig-welded aluminum diamond tread
- Heavy-duty tie-down rings
- Rugged steel support axle
- Power-coat finish wheel vise with durable, rubber padding
- Ergonomic crank for easy, non-damaging wheel security

SPECIFICATIONS

Platform width	28.5" (725 mm)
-----------------------	----------------

Platform length	88" (2,236 mm)
------------------------	----------------

Platform height	2.5" (57 mm)
------------------------	--------------

Ramp length	9.5" (241 mm)
--------------------	---------------

Max. Vice Width	8" (203 mm)
------------------------	-------------

Overall width (w/ crank)	28.5" (728 mm)
---------------------------------	----------------

Overall length (w/ clamp)	93" (2,362 mm)
----------------------------------	----------------

